



**GSAW2002**

# Ground System Architectures Workshop 2002

Alternative Operations Concepts

El Segundo, CA 13-15 March 2002



## Evolution of Knowledge-based Applications for Launch Support

Jeff Lankford  
Jeff.Lankford@aero.org



Alan Quan  
Alan.Quan@aero.org



GSAW2002

# Synopsis


- **Spacelift Telemetry Acquisition and Reporting System (The Aerospace Corporation developed and operated)**
  - Mission, History, and Environment
  - Forces shaping on-going evolution
- **Knowledge-based launch assessment**
  - Acknowledgements, Concept, and Process
  - Data, info, and knowledge: Sources and representations
- **Knowledge-based augmentation of architecture views**
  - Component, Layered, and Human interfaces
- **Knowledge-based launch support applications**
  - Heritage, Emerging, and Conjectured
- **Conclusions and Challenges**

 Experience suggests that unobtrusive knowledge-based applications can meet emerging launch support challenges 



GSAW2002

# STARS Mission




➡ Provide independent real-time and post-flight telemetry processing and analysis for a broad-spectrum of vehicles and operations ➡



GSAW2002

# STARS Evolution



# Real-time Launch Assessment Environment



GSAW2002



Courtesy The Aerospace Corporation



👉 Experts immersed in mission-control-like atmosphere 👈



GSAW2002

# Forces Shaping On-going Evolution

- **Reduced availability of expert domain specialists, due to:**
  - Increased launch frequency
  - New launch vehicles (different sub-systems and configurations)
  - Personnel turn-over (reduced effectiveness, lost knowledge)
- **Increased data load per launch, due to:**
  - New launch vehicles (more and faster sensors)
  - Greater network and workstation hardware speed
- **Evolving requirements, including:**
  - Reduce cost, time, errors; increase capability, performance, quality
  - Paradigm shift in customer / contractor relationship from “oversight” to “insight”; unattended 24/7 operations
- **Evolving software technologies, including:**
  - COTS vendors moving from proprietary to open interfaces (i.e., Talarian SmartSockets to JMS)
  - Object- and component-oriented tools (i.e., UML patterns, Java Swing GUI, and EJB distribution)



Many factors driving trend toward increased automation



# A Challenge Problem: Turbopump Spindown




GSAW2002



7 of 30

Determine the time it takes from the issued shutdown command for the turbopump to spin down to zero speed. Determine if any rubs occurred, as evident by a dramatic slope increase (both engines, both burns).



Typical “new requirements” with numeric and logical aspects






GSAW2002

# Sources of Uncertainty

- System transfers both linear and non-linear
- Noise both stationary stochastic and systemic
- No on-board time-stamps



$$O(t) = Nm(t) * [I(t) + A(t)] + \sum Na(t)$$

👉 Values precise, but inaccurate;  
Noise(s) masks carrier and anomalies in observed signal 👈



**GSAW2002**

# Knowledge-engineering Acknowledgements


- **Program support for knowledge-based applications engineering:**
  - Margaret Sazani, Bruce Mau, Pinfun Tsai, Joe Tomei, Ron Croyts
- **Engineering support for knowledge-based applications engineering:**
  - Ken Behring, Rich Gerardi, Manny Ruiz, Len Beck
- **Technical support for knowledge-based applications engineering:**
  - Paul Yuhas, Walt Green, Scott Zechiel, Brenda Kim, Don Sather, Regina Lozano, Susan Painter, Melodie Evans, Scott Turner, Charles Simmons

 A few of the many who contributed to the success of STARS 




GSAW2002



# Knowledge-based Assessment - Concept



Enhance user efficiency by automating tedious monitoring and analysis tasks and by focusing attention on exceptional conditions.



“Engine-1 turbine contacted housing 5.2 seconds after shutdown, lasting 0.2 seconds. Probably caused by overheated pump. No damage evident or expected; no action needed.”


 Automated detection, identification, diagnosis, prognosis, and recommendation 



GSAW2002

# Knowledge-based Assessment - Process

- 1) What symptoms are present?
- 2) What is the nature and origin of symptoms?
- 3) What might happen and what should be done?



- Launch information more limited than medical; launch only has observations, whereas medical has observation, inquiry, and lab tests.
- Launch observation is complicated: data is noisy, voluminous yet under-sampled/quantized, not precisely time-stamped
- Coordinating multiple knowledge-bases essential, for example systems engineering knowledge with signal processing.

👉 Launch assessment is vehicle health care insurance 👈



GSAW2002

# Data, Information, and Knowledge Sources and Representations

- **Data (facts)**
  - Sensor telemetry; databases w/ metadata (sample rates, quantization) and time-series data
  - Mission plans; tables of scheduled events with constraints
- **Information (patterns)**
  - Sensor time-series envelopes; mini-language for specifying rise & decay patterns
  - Family data statistics; computed derived time-series norms
- **Knowledge (reasoning)**
  - Vehicle sub-system behavior and physical constraints; engineering handbook tables and formulas
  - Anomaly assessment experience rules-of-thumb; ad-hoc constraints

➡ Increasing degrees of awareness; multiple mediums ➡



**GSAW2002**


# Characteristics of STARS Architecture

- **Human domain-specialists perform simple detection in real-time using electronic plots of sensor values, and plot comparisons for post-flight verification.**
- **A distributed processing system, enabled by voice and data communications.**
- **Applications inter-operate via data streams. Sensor data plotting is the primary application; others include scheduled event detection and flight visualization. Applications are implemented using tailored COTS and in-house code.**
- **Messaging infrastructure built on tailored COTS delivers data to applications using publish/subscribe paradigm and enables “plug-and-play” application modules.**
- **Real-time data is down-sampled, time-stamped packets from multiple sensors; full-rate archived data is also available.**



GSAW2002

# Component-interface Architecture View




👉 Nested closed-loop plants; incremental extension 👈



GSAW2002

# Layered-application architecture view




👉 “Plug-and-play” 👈




GSAW2002

# Human-interface Architecture View

### Typical STARS plot



### Augmented plot highlights deviations





GSAW2002

# Knowledge-based Applications - Legacy

- **Neural net based specialized anomaly detection**
  - Training data limited (few examples)
  - Limited identification (specific failures)
  - Inexplicable analysis, non-scalable approach
- **Code and rule based launch event detection**
  - Vehicle-specific, limited generalization of criteria leads to duplication of effort for implementation and maintenance
  - Simplistic, non-robust detection criteria may be inadequate if data is missing or corrupt
- **Integrated anomaly detection and reporting [7]**
  - Hyperlinks report with data



GSAW2002

# Neural Nets for Recognizing Known Anomalies


Neuralworks tool tailored to distinguish three (3) classes (good, bad, noise) from FFT input using three-layer back-propagation network (taken from [2]).

## Neural Nets: Real World Problem

### ▶ Failing IUS RIMU (Inertial Guidance Unit) data


- Sum Channel voltage showed anomalous behavior before failing
- Anomaly was not discovered launch testing causing expensive delay

## Failing RIMU Data




GOOD RIMU

BAD RIMU



## Neural Network Results






GSAW2002

# Rule-based Launch Event Detection

Gensym's G2 expert system shell tailored (rules at left) to detect Titan scheduled launch events (derived parameter times at far-right) using live telemetry and internal variables (at middle-right).





GSAW2002

# Integrated Anomaly Detection and Reporting [7]

The screenshot displays the ISTAR Telemetry Analysis Expert System interface. At the top, it shows system status including 'UNCLASSIFIED', 'MCR IDENTIFICATION: CPU LEADING', and a CPU usage graph. The main window is titled 'ANOMALY REPORT' and shows a detailed report for a specific event. The report text includes:

**ANOMALY REPORT**  
 PARAMETER IDENTIFICATION  
 TS=01:00:11:05

J-66-X-0088-E BRN 2 ARM CMC 4 (SERV2CMA) (SRM2CMA)  
 J-66-X-0088-E BRN 2 ARM CMC 3 (SERV2CMB) (SRM2CMB)

Update Rate (Hz): 6-H: 1.0 15-M: 0.5 3-24 (ARU): 1.0 3-24 (F7A)

Indicated the #34 (ST-2 Arm) relay matrix command to applying electronic bus power to the air side of the SRM motor-driven switch for SRM2 when in the high state (0.40 AM) as shown in Figure 2-1 (Table 4). Note that the #34 (SRM2 Arm C) relay matrix command must have been issued previously to enable the arming sequence. The relay will remain closed for the duration of the command (initially 1.001 seconds) which gives the SSR motor-driver switch sufficient time to move to the armed position. After the forward signal is removed at the end of the command, the SRM-2 arm command relay opens, and the SRM-2 Arm CMC arm and disarm to the low state (0.001 Hz).

The SRM-2 Arm CMC 4 measurement is taken from the contacts of SRM2 arm command relay in PDL 4, and the D measurement is taken from the contacts of the SRM-2 arm command relay in PDL 3. Since these measurements are high for only 1.004 seconds, it may not be reported on the 10 KHZ telemetry stream as the telemetry update rate is 1/3 Hz resolvable at 1 Hz!

At the bottom of the interface, there is a status bar with 'IGMT: 000:14834', 'EMCR 000:00:00:00', and 'UNCLASSIFIED'.

➡ [Anomaly report hyperlinks to telemetry](#) ➡



**GSAW2002**

# Emerging Knowledge-based Automation

- **Enhanced scheduled event and state detection**
  - Expectations based on mission plans and handbooks; parameterized generic plan
  - Reinforcing criteria (time, altitude, acceleration)
  - Feature-based signal envelopes for jitter rejection
- **Enhanced anomaly detection**
  - Expectations based on family norms (expected value, dynamic “red-line” bands)
  - Registered to event weigh-points



**GSAW2002**

# Sample Mission Scheduled Event Plan

**Event sequence      Physical basis      Measurand(s) values**

Code	Event description	Basis	Detection criteria
Ggi	Guidance go-inertial		
LVlo	Lift-off	2-inch motion	
PFj	Payload Fairing jettison	S1E1j + ? sec	CKR011C from 0 to 1 v in $0.1 \pm 0.01$ s; for $2 \pm 0.2$ s; to 0 v in $0.1 \pm 0.01$ s && CKR051C 0 to 1 v in $0.1 \pm 0.01$ s; for $2 \pm 0.2$ s; to 0 v in $0.1 \pm 0.01$ s
Ss	Spacecraft separation (may be after first or second burn)	{MECO 1 + ? sec} {MECO 2 + ? sec}	{CKS019C from 0 to 1 v in $0.02 \pm 0.002$ s; for $0.1 \pm 0.01$ s; to 0 v in $0.02 \pm 0.002$ s} {CKS075C from 0 to 1 v in $1 \pm 0.1$ s; for $0 \pm 0.001$ s; to 0 v in $1 \pm 0.1$ s}
S12s	Atlas / Centaur separation	S1E2j	CM_037D from 0 to 15 v in $1.5 \pm 0.15$ s; for $0.0 \pm 0.001$ s; to $1.0 \pm 1.0$ v in $0.2 \pm 0.02$ s && CKR114C from 0 to 1 v in $0.02 \pm 0.002$ s; for $0.25 \pm 0.025$ s; to 0 v in $0.02 \pm 0.002$ s
S1E1i	Booster ignition	LO - ? sec	
S1E1c	(BECO) Booster cutoff	5.0 g	AM_026D from 0 to 15 v in $0.7 \pm 0.1$ s; for $0.0 \pm 0.001$ s; to $2.5 \pm 2.5$ v in $0.02 \pm 0.002$ s
S1E1j	Booster jettison	BECO + 3.1 sec	
S1E2i	Sustainer ignition	LO - ? sec	
S1E2c	(SECO/VECO) Sustainer/Vernier c/o	propellant depletion	CKK976X from 0 to 1 v in $8.0 \pm 1.0$ s; for 0 s; to 1 v in 0 s
S1E2j	Sustainer jettison	SECO + 2 sec	
(S1E3l)	GL SRM pair ignition	LO - 0.51 sec	
(S1E3c)	GL SRM pair declared burnout	Sense acceleration drop + filter delay + $\Delta-t1$	
(S1E3j)	GL SRM pair jettison	$M > 1.2$ & $t > S1E4l + 3$ sec	
(S1E4l)	AL SRM pair ignition	S1E3c + ? sec	
(S1E4c)	AL SRM pair burnout	Sense acceleration drop + filter delay + $\Delta-t2$	
(S1E4j)	AL SRM pair jettison	S1E4c + ? sec	
S2E1i1	(MES 1) Centaur first burn	SECO + 18.5 sec	CKS081C from 0 to 1 v in $0.0 \pm 0.1$ s; for 0 s; to 1 v in 0 s
S2E1c1	(MECO 1) Centaur first cutoff	initiated by INU when parking orbit achieved	
S2E1i2	(MES 2) Centaur second burn	initiated by INU when trajectory correct	
S2E1c2	(MECO 2) Centaur second cutoff	initiated by INU when trajectory correct	
S1m1b	Roll program start	LO + 8 sec	
S1m1e	Roll program stop	LO + 15 sec	
S2m1b	Attitude align & spin start		
S2m1e	Attitude align & spin stop		

 [Launch event/state ontology, formal criteria specification](#) 



GSAW2002

# Mission Event Reporting

discrete\_event\_list4:

**Titan IV B34 Mission Event List**  
**STAGE 2 FLIGHT EVENTS**

PRINT EXIT

Event	Value / Status	Predicted Time	Actual Time
<b>Enable Stage 2 Shutdown</b>	(FTS DISC STAGE 2 S/D ENABLE RELAY A IND - TD260)	0.00	0.00
(TD286 ON) <b>OFF</b>			
(TD394 ON) <b>OFF</b>			
	STG2 S/D ENABLE RLY A - TD260 0		
	STG2 S/D ENABLE RLY B - TD261 0		
**** STAGE 2 COMMAND SHUTDOWN ****			
<b>Enable Stage 2 FTS Safing</b>		(GCU DISCRETE #13) 0.00	0.00
(GD013 ON) <b>OFF</b>	(GD018 ON) <b>OFF</b>	(GCU DISCRETE #18) 0.00	0.00
(GD037 ON) <b>OFF</b>	(GD042 ON) <b>OFF</b>	STG2 SHUTDOWN RLY A 0 (GCU DISCRETE #37) 0.00	0.00
		STG2 SHUTDOWN RLY B 0 (GCU DISCRETE #42) 0.00	0.00
<b>Stage 2 FTS Safing</b>			
(GD019 ON) <b>OFF</b>	STG2 FTS SAFING RLY A 0	(GCU DISCRETE #19) 0.00	0.00
(GD043 ON) <b>OFF</b>	STG2 FTS SAFING RLY B 0	(GCU DISCRETE #43) 0.00	0.00
<b>Stage 2 Retro Rockets On/Off</b>			
(GD020 ON) <b>OFF</b>	(GD021 ON) <b>OFF</b>	<b>Retros On</b> (GCU DISCRETE #20) 0.00	0.00
(GD044 ON) <b>OFF</b>	(GD045 ON) <b>OFF</b>	(GCU DISCRETE #44) 0.00	0.00
		<b>Retros Off</b> (GCU DISCRETE #20) 0.00	0.00
		(GCU DISCRETE #44) 0.00	0.00
***** SV SEPARATION *****			
		(GCU DISCRETE #22) 0.00	0.00
		(GCU DISCRETE #46) 0.00	0.00
		(GD022 ON) <b>OFF</b>	(GD023 ON) <b>OFF</b>
		(GD046 ON) <b>OFF</b>	(GD047 ON) <b>OFF</b>



Stg 2 Long Truss Accels

👉 Highlight actual exceptions to predicted 👈



GSAW2002

# Applying Family Statistics Models



👉 Highlight exceptions to statistical norms 👈

# Conjectured Knowledge-based Automation




GSAW2002

- **Advanced Knowledge-based Anomaly Analysis**
  - Augments and corroborates statistical analysis
  - Model-based reasoning
  - Anomaly detection
  - Anomaly diagnosis
- **Decision support for people**
  - Provide recommendations for corrective and preventive action (sometimes just leave it be)
  - Depends on good diagnosis, which depends on good identification
- **No monolithic tool**
  - Generic and specialized (broad) model-based expert systems
  - Coordinated expert systems
  - Synthesized views composed from vehicle subsystems models



GSAW2002

# Key Knowledge-based Assessment Elements





# Example Coordinated Knowledge-based Models




Figure 1: Top-Level BEAM Architecture (taken from [6])



GSAW2002

# Conclusions and ...

- **Real-world operations**

- Too much data, not enough information (noise, lack of time-stamps, down-sampled data, lack of telemetry standards (but see [1]))
- People (clever pattern recognizers, but error-prone; they don't know what they know)
- Extensible, data-centric architecture enable unobtrusive technology insertion (not just for plotting!)

- **Trouble, yes sir, right here in River City**

- Where have all the people gone?
- What, more launches?
- Future shock (better, faster, cheaper)

- **Successes, more or less**

- We've learned some things about what doesn't work
- We've learned some things about what works
- We've learned some things about what could work



GSAW2002

## ... and Challenges

- **No single technique is a “magic bullet”**
  - Distinguishing signals (events and anomalies) masked by noise requires both numeric and symbolic analysis
  - Coordination of multiple knowledge sources and techniques is essential for robust detection and diagnosis
  - Trade space (and pre-processing time) for time
- **Model-based reasoning offers a solid foundation**
  - Has been used successfully for automated anomaly detection and diagnosis in production systems
  - Multiple models provide a variety of perspectives on vehicle health and status, offering a more comprehensive view than any single-model approach.
- **Need sophisticated coordination techniques (~ voice)**
  - Need to codify expert knowledge from unpublished sources
  - Need more robust numerical, signal processing, statistical analysis, and fuzzification
  - Need synchronization with logical, discrete, and modal analysis



GSAW2002

# References

- [1] D Ernst, & A Hooke, “The Real-Time Telemetry Networks Initiative”, GSAW 2001, El Segundo CA CA, Feb 2001.
- [2] W Green, “Neural Networks and Telemetry Fault Analysis”, Aerospace briefing, El Segundo CA, Feb 1996.
- [3] S Isakowitz [ed], “International Reference Guide to Space Launch Systems”, AIAA, Washington DC, 1995.
- [4] Lankford, et al, “Engineering SUR Software Architecture Evolution”, STARS Summit, El Segundo CA, Jun 2001.
- [5] W Larson & J Wertz [ed], “Space Mission Analysis and Design”, Microcosm and Kluwer, 1992.
- [6] R Mackey, *et al*, “BEAM: Technology for Autonomous Self-Analysis,” *2001 IEEE Aerospace Conference*, Big Sky MT, Mar 2001.
- [7] Simmons, C, “Intelligent System for Telemetry Analysis in Real Time”, Aerospace Technical Report, El Segundo CA, Oct 1993.